

ENOC ACTIVE SYN OEM

PRODUCT DESCRIPTION

ENOC ACTIVE SYN OEM is a 100% synthetic automatic transmission fluid designed specifically for use in passenger cars and selected commercial vehicles automatic transmission with outstanding contribution to fuel economy performance in American, Japanese, Korean and European equipment. **ACTIVE SYN OEM** provides the excellent friction durability and anti-shudder performance required by GM, Ford, AISIN transmission manufacturers and many others.

APPLICATIONS

ENOC Active SYN OEM can be used in North American, European, and Asian vehicles. It is compatible with most high performance stepped automatic transmissions and provides premium performance in older vehicles. Active SYN OEM is developed for LOW viscosity applications:

- ◆ Passenger car automatic transmissions and power steering
- ◆ Commercial vehicle automatic transmission and power steering
- ◆ Off-highway and construction equipment automatic transmissions
- ◆ Hydraulics

PERFORMANCE STANDARDS

ACTIVE SYN OEM is suitable for the following OEM and International specifications:

Aisin Warner JWS 3309 (T-IV) & JWS 3324 (WS)	Audi G 052 162-A1/A2	Audi G 055 025 A2 (JWS 3309)
Audi 5 HP LT71141 (ZF 5 HP 18FL/19FL/24A)	Suzuki AT OIL 5D06, ATF 2326, ATF 2384K, JWS 3309, ATF 3314, ATF 3317	VW 5 HP (ZF 5 HP 30), (18FL, 30), (19FL, 24A), G-055-025 A2 (JWS 3309), TL 521 62
BMW JWS 3309 (T-IV), LA2634, LT71141 (ZF 5 HP 18FL/19FL/24A), ZF 5HP18FL, 5HP24, 5HP30, 7045E, ETL-80728, MINI	GM TASA, DEXRON*-II, DEXRON*-IID, DEXRON*-IIE, DEXRON*-IIIG, DEXRON*-IIIH	ZF all 3 & 4 speed transmission, TE-ML 09, 09X, 11A, AAB
Ford MERCON*, FNRS, WSS-M2C138CJ, WSS-M2C166H, WSS M2C 922A1, 924A (XT-8-QAW) JWS 3309	Hyundai/Kia AP-IV, SP-IV M, SP-IV-RR, SP-III, Dex-II/SP-II, JWS 3314, JWS 9683	Mazda ATF D-II, ATF M-III, ATF M-V, ATF FZ, ATF F-1, ATF S-1, ATF N-1, ATF 3317
Volvo CE 97340	Honda ATF-Z1 (except in CVTs), DW-1	Fuso ATF-II, ATF-SPIII, ATF-A4
Hino Blue Ribbon ATF	Subaru ATF, ATF 5AT, DEXRON*-II, ATF HP	Lexus JWS 3309
Chrysler ATF+, +2, +3 (MS 7176E), +4 (MS 9602)	Chrysler/Dodge MOPAR AS 68 RC (T-IV), JWS 3309	Mitsubishi Diaqueen SK, SP-II, SP-III, SP-IV, AW, J2, J3, ATF PA
Peugeot ZF 4HP20	ISUZU , BESCO ATF-II, ATF-III	Allison C-3 & C-4
Porsche , ZF 5HP19FL, ZF 5HP20, LT71141, ATF 3403-M115, T-IV (JWS 3309)	Jaguar ATF 3403 M115, ATF 3403-M115, ATF LT71141, ZF 5HP24, JLM20238	MB 236.1, 236.2, 236.3, 236.5, 236.6, 236.7, 236.8, 236.9
Daihatsu AMMIX ATF D-II, AMMIX ATF D-III SP	JASO M315-2013 1A, 1A-LV, 2A	Nissan Matic Fluid C, D, J, K, S
Toyota ATF D-II, D-III, T-III, T-IV, WS	JEEP ATF+3, +4	MINI COOPER T-IV

Always follow equipment manufacturer's recommendation for required lubricant performance levels and oil drain intervals.

Issued by ENOC Marketing LLC, Dubai, U.A.E

Last updated on September 2024 – MS

PDS V5250924

BENEFITS

ACTIVE SYN OEM provides:

- ◆ Suitable for multi vehicle Automatic Transmission
- ◆ Excellent friction durability and anti-shudder performance
- ◆ Extended long drain intervals
- ◆ Very good low temperature fluidity

Technical Data*	
Color	Red
Density at 29.5 °C, g/cc	0.8337
Viscosity mm ² /s @ 100°C	7
Viscosity mm ² /s @40°C	36.87
Brookfield @-40°C, cP	15440
Flash Point, °C	210
Viscosity Index	157
Pour Point, °C	-42
Product Code	221009

*The information prepared provides the typical properties that are considered as representative. Some variation which will not affect performance is possible.

HEALTH AND SAFETY, ENVIRONMENT

The information on this product is available in the ENOC Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information we recommend you review the MSDS. Handled correctly there are no special precautions suggested.

Issued by ENOC Marketing LLC, Dubai, U.A.E

Last updated on September 2024 – MS

PDS V5250924