

ENOC PROTEC X-TREME

PRODUCT DESCRIPTION

ENOC PROTEC X-TREME is an advanced technology **fully synthetic lubricant** for the latest model passenger cars requiring performance specification API SP, ACEA A3/B4 developed to provide maximum protection for all passenger cars, including high performance cars and cars with low emission engines with catalytic converts fitted to the vehicles. It is available in several viscosity grades to provide maximum engine protection and to meet long drain requirements. Compatible for all cars running on lead free gasoline as well as diesel passenger cars with variable fuel quality (without DPF).

APPLICATIONS

- ◆ All new makes of passenger cars requiring API SP / ACEA A3/B4
- ◆ High performance cars normally aspirated and turbocharged gasoline engines
- ◆ Cars fitted with exhaust catalytic converts to meet low emission requirements
- ◆ Latest model Japanese, American and European cars.

PERFORMANCE STANDARDS

PROTEC X-TREME meets and exceeds the following International specifications:

API	SP	MB Approval	229.5
ACEA	A3/B4	BMW	Long-life Oi LL-01
VW	502.00/505.00	Porsche	A40
PSA	B71 2296	Renault	RN0700/0710

Always follow equipment manufacturer's recommendations for required lubricant performance level and oil drain intervals.

BENEFITS

PROTEC X-TREME provides:

- ◆ Fully Synthetic formula for extended drain intervals & also ensuring excellent engine protection
- ◆ Approved to various global OEM/Industry body specifications
- ◆ Suitable for latest technology engines including turbocharged, direct injection gasoline engines, light duty diesel engines & Hybrids.

Technical Data*		
SAE Grade	0W-40	5W- 40
Density at 15°C, g/mL, ASTM D4052	0.8532	0.8449
Viscosity, Kinematic, ASTM D 445		
mm ² /s at 40°C	74.95	84.25
mm ² /s at 100°C	13.3	14.1
Viscosity Index	180	170
Pour Point, °C, ASTM D97	-39	-39
Flash Point, °C, ASTM D92	228	228
Product code	210106	210105

*The information prepared provides the typical properties that are considered as representative. Some variation which will not affect performance is possible

HEALTH AND SAFETY, ENVIRONMENT

The information on this product is available in the ENOC Material Safety Data Sheet (MSDS) as a guide to the precautions and safe handling of this product and its disposal. For further information we recommend you review the MSDS. Handled correctly there are no special precautions suggested.